

wall mounting socket outlet - housing dimensions 126x83



| Product description | |
|---------------------------|--------------------------------|
| BALS-Prd.-Nr | 106 |
| EAN | 4024941001069 |
| Product group | GT wall mounting socket outlet |
| Current | 16A |
| Number of poles | 5p |
| Arrangement of the phases | 3P+N+PE |
| Earth 'clock' position | 6 h |
| Voltage | 200/346 up to 240/415V |
| Frequency | 50 and 60Hz |

| Product description | |
|------------------------|--|
| Protection degree | IP44 |
| Colour code | red |
| Colour of appliance | Hinged lid red, Housing bottom grey, Housing top grey, Collar grey |
| Connection design | screw terminal |
| Maximum conductor size | 4,0 qmm |
| Cable entry | M25 |
| Height | 154mm |
| Width | 83mm |
| Depth | 130mm |
| Dimension of enclosure | 126x83 mm (HxW) |
| Material of enclosure | Polyamide |
| Contacts | The contact carrier is made of polyamide, The contacts are brass |

| Additional technical information | |
|----------------------------------|---|
| | The cable entry is one at top open and two at bottom closed |
| | Lower part of housing rotatable by 180° |
| | 4 cut out fixing holes in the lower part of housing |

| Logistics data | |
|----------------|-----------------|
| Weight/pcs | 0.32 kg / Piece |
| Packaging | Bag |

| Logistics data | |
|----------------|---------------|
| Content amount | 1 ST |
| EAN | 4024941001069 |
| Length | 410 mm |
| Width | 285 mm |
| Weight | 0.321 kg |
| Packaging | Carton |
| Content amount | 10 ST |
| EAN | 4024941968553 |
| Length | 330 mm |
| Width | 216 mm |
| Height | 260 mm |
| Weight | 3.426 kg |
| Volume | 17,062.5 ccm |



1 MB 2

| Ampere Polzahl | 16 4 | 16 5 | 32 3 | 32 4 | 32 5 |
|----------------------------|---------|---------|---------|---------|---------|
| a | 83,0 | 83,0 | 83,0 | 83,0 | 83,0 |
| b | 126,0 | 126,0 | 126,0 | 126,0 | 126,0 |
| c | 153,0 | 155,0 | 155,0 | 155,0 | 155,0 |
| d | 127,0 | 130,0 | 130,0 | 130,0 | 136,0 |
| e | 68,0 | 68,0 | 68,0 | 68,0 | 68,0 |
| f | 11,0 | 11,0 | 11,0 | 11,0 | 11,0 |
| h ø | 5,5 | 5,5 | 5,5 | 5,5 | 5,5 |
| i | 6,5 | 6,5 | 6,5 | 6,5 | 6,5 |
| k ø | 12,0 | 12,0 | 12,0 | 12,0 | 12,0 |
| l | 65,0 | 65,0 | 65,0 | 65,0 | 65,0 |
| m | 80,0 | 80,0 | 80,0 | 80,0 | 80,0 |
| n ø | 10,0 | 10,0 | 10,0 | 10,0 | 10,0 |
| o | M25 | M25 | M25 | M25 | M25 |
| p | 2 x M25 | 2 x M25 | 2 x M25 | 2 x M25 | 2 x M25 |
| Leiter mm ² min | 1,5 | 1,5 | 2,5 | 2,5 | 2,5 |
| Leiter mm ² max | 4 | 4 | 10 | 10 | 10 |