PHILIPS

CorePro LED PLC CorePro LED PLL compatibility list Professional Q3 2018

Table of content

11/2

Philips CorePro LED PLC

•	Philips CorePro LED PLC 4.5W 8xx 4P G24q-1	2
---	--	---

- Philips CorePro LED PLC 6.5W 8xx 4P G24q-2
- Philips CorePro LED PLC 9.0W 8xx 4P G24q-3

Philips CorePro LED PLL

Philips CorePro LED PLL HF 16W 8xx 4P 2G11
5

7

Philips CorePro LED PLL HF 24W (55) 8xx 4P 2G11

Philips CorePro LED PLC 4.5W 8xx 4P G24q-1

Ballast Compatibility



KEY

Ballast is compatible	Th
Ballast is not compatible, will not work according to Philips claimed specifications	

		This document is for information purposes and must be treated as recommendation. Philips attempted to provide best results, results are generated in lab controlled environment and may differ from actual application conditions
--	--	--

				CorePro LED PLC 4.5W 8xx 4P G24q-1 Model number: 9290013510 9290013511
	Ballast type	10nc	Lamps on ballast	AC (50Hz) on HF Ballast Compatible
	HF-M 113 TL/PLS/PLC SH	9137004137	1	
	HF-M 113 TL/PLS/PLC LH	9137004139	1	
	BLUE 114 LH TL/PLS/PLC	9137004217	1	
PHILIPS	RED 114 SH TL/TL5/PLC/S	9137004232	1	
H	HF-P113-17 PL-T/C/R EII	9137006311	1	
	HF-P 2 13-17 PL-T/C/R EII	9137006312	2	
	EB-C 113 PL-T/C 220	9137131984	1	
	EB-C 213 PL-T/C 220	9137131985	2	
	QT-ECO 1X4-16/220-240 L		1	
Σ	QT-ECO 1X4-16/220-240 S		1	
OSRAM	QTP-D/E 1X10-13		1	
0	QTP-D/E 2X10-13		2	
ᆠᇥ	ELXc 213.870	188698	2	
VOSSLOH- SCHWABE	ELXc 213.870	188698	1	
VOS	ELXs 121.901	188663	1	
	ELXs 121.904	188664	1	
	PCA 1x11/13 TC EXCEL one4all	22185134	1	
	PCA 1x11/13 TC ECO	22185126	1	
	PCA 2x11/13 TC EXCEL one4all	22185135	2	
TRIDONIC	PCA 2x11/13 TC ECO	22185127	2	
TRID	PC 1x5-16W BASIC	24138830	1	
	PC 1x5-16W BASIC sl	24138833	1	
	PC 1/2x9-13 TC PRO	22176405	2	
	PC 1/2x9-13 TC PRO	22176405	1	
	BCD13.1-2Q-01/220-240/1-10V	10096393	2	
	BCD13.1-2Q-01/220-240/1-10V	10096393	1	
	BCS21.1-2LS-01/220-240	10095043	2	
0	BCS21.1-2LS-01/220-240	10095043	1	
BAG HUECO	BCS21.1-2Q-01/220-240	10097543	2	
로	BCS21.1-2Q-01/220-240	10097543	1	
BAG	BCS21.1-2QI-01/220-240	10095743	2	
	BCS21.1-2QI-01/220-240	10095743	1	
	EBS21.1C-01/220-240	10050990	1	
	EBS21.1M-01/220-240	10050994	1	
	EBS16.1C-01/220-240	10050989	1	
	BCC 121	137946HTC	1	
	BCC 121/2	137969/21MM	1	
	BCC 121/2 SL	137944/21H	1	
	BCC 121 SL	137944B/21H	1	
10	BCC 121 IP54	137969IP21MM	1	
	MBQ 113/2	137968/113	1	
	MB213	137988/213	2	
	MB213/2	137988/2132	2	
	MBQ 213/2	137968/213	2	

General note Philips CorePro LED PLC

General notes: Refer to the product reference number in the header of the columns to use this product-ballast compatibility list.

Please note that Philips CorePro LED PLC 4P are only tested with HF ballast on AC operation. The performance of Philips CorePro LED PLC 4P on HF ballasts with DC operation is not tested and is therefore not guaranteed. Philips CorePro LED PLC 4P range is designed to work on HF ballasts only. For EM ballasts configuration, please contact a Philips sales representative for more information on our EM compatible range.

This document is for information purposes only and must be treated as recommendation. Philips will not accept claims for any damage caused by not implementing the recommendations in this document. Philips does not accept any responsibility, warranty or liability when using Philips CorePro LED PLC 4P with ballasts not mentioned in this list, or when using successor models of the tested ballasts. Although Philips aims to provide the most accurate information and test results from controlled experiments the results may vary in different applications. This document focuses on the behaviour of above mentioned Philips CorePro LED PLC 4P. Please also check and follow the instructions of HF ballast manufacturers for installation instructions.

Dimming: Philips CorePro LED not developed for dimming therefore the performance cannot be guaranteed in a dimming application. In case of usage of a non-dimmable product in a dimmable application, warranty does not apply

PHILIPS

Philips CorePro LED PLC 6.5W 8xx 4P G24q-2

Ballast Compatibility



KEY

Ballast is not compatible, will not work according to Philips claimed specifications	This document is for information purposes and must be treated as recommendation. Philips attempted to provide best results, results are generated in lab controlled environment and may differ from actual application conditions
	CorePro LED PLC 6.5W 8xx 4P G24q-2 Model number: 9290012010 9290012011

Image: space					9290012011
Pri-2 B PL-TC II. 202-2407 S0/K0/Hz 912700484 1 Philos FMP LDI 185 PL/CT 1202-2407 S0/K0/Hz 912700318 2 H-F 3 B PL-TC (1 SB 220-2407 S0/K0/Hz 912700338 2 H-F 5 2B PL-TC (1 SB 220-2407 S0/K0/Hz 912700533 2 H-F 5 2B PL-TC (2 B) 240-2407 S0/K0/Hz 912700533 2 H-F 5 2B PL-TC (2 B) 240-2407 S0/K0/Hz 912700530 1 H-F 2 B PL-TC (2 B) 240-2407 S0/K0/Hz 912700530 2 OT PLTE DBL8, 208 Sngle 1 2 OT-FTE DBL8, 208 Sngle 1 2 OT-FTE DBL8, 208 Sngle 1 2 OT PLTE DBL8, 208 SN LDAH 10 2 OT PLTE DBL8, 208 SN LDAH 10 2 VEX LS 200 H3/H3/HW 186694 1 EX 248 711/24 HV - DAH 1000724 1 FV 248 FC FRO S - DAH 2270412 1 <tr< th=""><th></th><th>Ballast type</th><th>10nc</th><th>Lamps on ballast</th><th>AC (50Hz) on HF Ballast Compatible</th></tr<>		Ballast type	10nc	Lamps on ballast	AC (50Hz) on HF Ballast Compatible
NumberNumbe		HF-P 118 PL-T/C III 220-240V 50/60Hz	9137006485	1	
Special In F-5 28 FL-7C (1 SP 320-240V \$0,060Hz) 913710358 2 HF-5 18 FL-7C C IS P320-240V \$0,060Hz 913710353 2 HF-7 10 SF 128 L-7C C IS P320-240V \$0,060Hz 913710533 2 HF-7 12 SF L-7C C 20-20 U SC 0.060Hz 913700533 2 HF-7 28 FL-7C C IS P3 L-7C C 20-20 U SC 0.060Hz 913700530 1 HF-7 28 FL-7C 28 Hz-7C 20-20 U SC 0.060Hz 913700530 1 U T-7E TABLS, 2XB - Single 1 1 QTF-7C TZ X8H220-240 2 2 Quebtooic QT-70C X8H 220-240 2 2 V V X8H XT PRO - Single 188663 1 V V X8H XT PRO - Single 107239 2 V V X2H XT PRO - Single 107239 2 V V X2H XT C PRO - Single <t< td=""><td></td><td>HF-P 218 PL-T/C III 220-240V 50/60Hz</td><td>9137006486</td><td>2</td><td></td></t<>		HF-P 218 PL-T/C III 220-240V 50/60Hz	9137006486	2	
Pi-P 208 PL-YC 20-24091700 01532HP-P 208 PL-YC 21191700 05301HP-P 208 PL-YC 21191700 055002TOP YE 10129170 055002TOP YE 10129170 05102TOP YE 10129170 05101TOP YE		Philips HF-M RED 118 SH PLC/PL-T 230-240V	9137004234	1	
Pi-P 208 PL-YC 20-24091700 01532HP-P 208 PL-YC 21191700 05301HP-P 208 PL-YC 21191700 055002TOP YE 10129170 055002TOP YE 10129170 05102TOP YE 10129170 05101TOP YE	Sal	HF-S 218 PL-T/C II SR 220-240V 50/60Hz	9137130358	2	
HF-P18PL-T/C EII 913706309 1 HF-P28PL-T/C EII 9137006300 2 OTP-T/E X18, 2X18 - Single 1 2 OTP-T/E X18, 2X18 - Dual. 2 2 OTP-T/E X18, 2X18 - Dual. 1 2 OTP-T/E X18 20-20.00 1 OTP-T/E X18 18664 1 EXX 513001 M3/8W 188664 1 EXX 513001 M3/8W 188664 1 EXX 513001 M3/8W 188699 2 EXX 513001 M3/8W 188699 2 EXX 513001 M3/8W 100729 1 FV 2X88 TC FRO - Single 227646 1 PC 1X38 TC FRO - Single 307239 2 PC 1X38 TC FRO - Single 2006073 1 FX 1X8 TC FRO - Single 2006074 2 FX 1X8 TC FRO - Single 1009754	H	HF-S 118 PL-T/C II SR 220-240V 50/60Hz	9137130359	1	
Image: space s		HF-P 218 PL-T/C 220-240	9137001553	2	
VPTOF CV2XBTCPR0 s- Single I PC V2XBTCPR0 s- Single 1 2 PC V2XBTCPR0 s- Single 1 2 PC V2XBTCPR0 s- Single 276446 1 PC V2XBTCPR0 s- Single 277646 2 PC V2XBTCPR0 s- Single 277646 1 PC V2XBTCPR0 s- Single 277646 1 PC V2XBTCPR0 s- Single 277646 1 PC V2XBTCPR0 s- Single 277646 2 PC V2XBTCPR0 s- Single 277646 2 PC V2XBTCPR0 s- Single 2776476 2 PC V2XBTCPR0 s- Single 2776472 1 PC V2XBTCPR0 s- Single 2776472 1 PC V2XBTCPR0 s- Dual 10097544 1 PC V2XBTCPR0 s- Dual 10097544 2		HF-P 118 PL-T/C EII	9137006309	1	
OPP-/FE X18, 2X8 - Dual I I QFP-/FE X18, 2X3 - 240 I I Quicktron; QF-/JE X18/ 230 - 240 I I QUP-/FE X18 I I QP-/FE X18 I I QUP-/FE X18 I I QP-/FE X18 I I QP-/FE X18 I I QUEXTON; QP-/FE X18 I I I EX IS 21901 M3/18W I I I EX IS 218.711/2x18W - Single I I I EX 218.871 V2x18W - Dual I I I I PC 1/2x18 TC PRO - Single I I I I PC 1/2x18 TC PRO - Single I I I I PC 1/2x18 TC PRO - Single I I I I <tr< td=""><td></td><td>HF-P 218 PL-T/C EII</td><td>9137006310</td><td>2</td><td></td></tr<>		HF-P 218 PL-T/C EII	9137006310	2	
Not the second		QTP-T/E 1X18, 2X18 - Single		1	
Quektronic Q1-D/E kilk / 230-240 Image: Control of Control	Σ	QTP-T/E 1X18, 2X18 - Dual		2	
Quektronic Q1-D/E kilk / 230-240 Image: Control of Control	SRA	QT-ECO T/E 2X18/220-240		2	
LXs 121.901 ht/3/18W IR8663 1 ELXs 121.904 ht/3/18W 188664 1 ELXs 121.904 ht/3/18W Single 188669 1 ELXs 218.871 /2x18W - Single 188699 1 1 ELXs 218.871 /2x18W - Dual 188699 2 1 PC 1/2x18 TC PR0 sr - Single 22176416 2 1 PC 1/2x18 TC PR0 sr - Dual 22176416 2 1 PC 1/2x18 TC PR0 sr - Single 1307239 1 1 PC 1/2x18 TC PR0 sr - Single 22000073 1 1 PC 1/2x18 TC PR0 sr - Single 22176412 1 1 PC 1/2x18 TC PR0 sr - Single 22176412 1 1 PC 1/2x18 TC PR0 sr - Single 22176412 1 1 PC 1/2x18 TC PR0 sr - Single 2176412 2 1 PC 1/2x18 TC PR0 sr - Single 10097544 1 1 BCS181-2Q-01 / 220-240 1/2x TC-DEL/-TEL 18W - Single 10095044 1 1 BCS181-2Q-01 / 220-240 1/2x TC-DEL/-TEL 18W - Single 10095044 2 1	0	Quicktronic QT-D/E 1x18 / 230-240		1	
Bits ELXs 121.904 ht/3/18W IB8664 1 ELX 218.871 //2x18W - Single 188699 1 ELX 218.871 //2x18W - Single 188699 2 PV //2x18 TC PRO sr - Single 22176416 1 PC 1/2x18 TC PRO sr - Dual 2176416 2 PC 1/2x18 TC PRO - Dual 1307239 2 PC 1/2x18 TC PRO sr - Dual 1307239 2 PC 1/2x18 TC PRO sr - Single 22176412 1 PC 1/2x18 TC PRO sr - Single 22176412 1 PC 1/2x18 TC PRO sr - Single 22176412 1 PC 1/2x18 TC PRO sr - Single 22176412 1 PC 1/2x18 TC PRO sr - Single 22176412 1 PC 1/2x18 TC PRO sr - Dual 2017544 2 PC 1/2x18 TC PRO sr - Dual 10097544 2 PC 1/2x18 TC - DEL/-TEL 18W - Single 10095044 1 BCS181-2C - 01 / 220 - 240 1/2x TC - DEL/-TEL 18W - Single 10095044 2 BCS181-2C - 01 / 220 - 240 1/2x TC - DEL/-TEL 18W - Single 10095044 2 BC11/2x18TC Sr Single L1/2x18V - Single 1<		QTP-T/E 2x18		2	
ELX: 218.871 1/2x18/W - Dual1886992PC 1/2x18 TC PRO sr - Single21764161PC 1/2x18 TC PRO Sr - Dual21764162PC 1/2x18 TC PRO Sr - Dual13072391PC 1/2x18 TC PRO Sr - Dual13072392PC 1/2x18 TC PRO Sr - Single280000731PC 1/2x18 TC PRO Sr - Single20000731PC 1/2x18 TC PRO Sr - Single21764121PC 1/2x18 TC PRO Sr - Single21764121PC 1/2x18 TC PRO Sr - Single100975441PC 1/2x18 TC PRO Sr - Dual100975442PC 1/2x18 TC PRO Sr - Dual100975441PC 1/2x18 TC PRO Sr - Dual100975442PC 1/2x18 TC PRO Sr - Dual100975442PC 1/2x18 TC PRO Sr - Dual100950441PC 1/2x18 TC PRO Sr - Dual100950441PC 1/2x18 TC S PC 240 1/2x TC-DEL/-TEL 18W - Dual100950441PC 1/2x18 TC S - Dual100950442PC 1/2x18 TC S - Dual22PC 1/2x18 TC S - Dual100950442PC 1/2x18 TC S - Dual100950442PC 1/2x18 TC S - Dual100950442PC 1/2x18 TC S - Dual12PC 1/2x18 TC S - Dual2PC 1/2x18 TC S - Dual1PC 1/2x18 TC S - Dual137968/118PC 1/2x18 TC S - Dual1379		ELXs 121.901 1x13/18W	188663	1	
ELX: 218.871 1/2x18/W - Dual1886992PC 1/2x18 TC PRO sr - Single21764161PC 1/2x18 TC PRO Sr - Dual21764162PC 1/2x18 TC PRO Sr - Dual13072391PC 1/2x18 TC PRO Sr - Dual13072392PC 1/2x18 TC PRO Sr - Single280000731PC 1/2x18 TC PRO Sr - Single20000731PC 1/2x18 TC PRO Sr - Single21764121PC 1/2x18 TC PRO Sr - Single21764121PC 1/2x18 TC PRO Sr - Single100975441PC 1/2x18 TC PRO Sr - Dual100975442PC 1/2x18 TC PRO Sr - Dual100975441PC 1/2x18 TC PRO Sr - Dual100975442PC 1/2x18 TC PRO Sr - Dual100975442PC 1/2x18 TC PRO Sr - Dual100950441PC 1/2x18 TC PRO Sr - Dual100950441PC 1/2x18 TC S PC 240 1/2x TC-DEL/-TEL 18W - Dual100950441PC 1/2x18 TC S - Dual100950442PC 1/2x18 TC S - Dual22PC 1/2x18 TC S - Dual100950442PC 1/2x18 TC S - Dual100950442PC 1/2x18 TC S - Dual100950442PC 1/2x18 TC S - Dual12PC 1/2x18 TC S - Dual2PC 1/2x18 TC S - Dual1PC 1/2x18 TC S - Dual137968/118PC 1/2x18 TC S - Dual1379		ELXs 121.904 1x13/18W	188664	1	
ELX: 218.871 1/2x18/W - Dual1886992PC 1/2x18 TC PRO sr - Single21764161PC 1/2x18 TC PRO Sr - Dual21764162PC 1/2x18 TC PRO Sr - Dual13072391PC 1/2x18 TC PRO Sr - Dual13072392PC 1/2x18 TC PRO Sr - Single280000731PC 1/2x18 TC PRO Sr - Single20000731PC 1/2x18 TC PRO Sr - Single21764121PC 1/2x18 TC PRO Sr - Single21764121PC 1/2x18 TC PRO Sr - Single100975441PC 1/2x18 TC PRO Sr - Dual100975442PC 1/2x18 TC PRO Sr - Dual100975441PC 1/2x18 TC PRO Sr - Dual100975442PC 1/2x18 TC PRO Sr - Dual100975442PC 1/2x18 TC PRO Sr - Dual100950441PC 1/2x18 TC PRO Sr - Dual100950441PC 1/2x18 TC S PC 240 1/2x TC-DEL/-TEL 18W - Dual100950441PC 1/2x18 TC S - Dual100950442PC 1/2x18 TC S - Dual22PC 1/2x18 TC S - Dual100950442PC 1/2x18 TC S - Dual100950442PC 1/2x18 TC S - Dual100950442PC 1/2x18 TC S - Dual12PC 1/2x18 TC S - Dual2PC 1/2x18 TC S - Dual1PC 1/2x18 TC S - Dual137968/118PC 1/2x18 TC S - Dual1379	/OSS	ELXc 218.871 1/2x18W - Single	188699	1	
PC 1/2x18 TC PRO sr - Dual221764162PC 1/2x18 TC PRO - Single13072391PC 1/2x18 TC PRO - Dual13072392PC 1/2x18 TC PRO - Dual280000731PC 1/2x18 TC TOP280000732PC 1/2x18 TC PRO sr - Single20000742PC 1/2x18 TC PRO sr - Single21764121PC 1/2x18 TC PRO sr - Dual21764122PC 1/2x18 TC PRO sr - Dual21764122PC 1/2x18 TC PRO sr - Dual100975442BCS18.1-2Q-01 / 220-240 1/2x TC-DEL/-TEL 18W - Single100975442BCS18.1-2LS-01 / 220-240 1/2x TC-DEL/-TEL 18W - Single100950442BCS18.1-2LS-01 / 220-240 1/2x TC-DEL/-TEL 18W - Single100950442BCS18.1-2LS-01 / 220-240 1/2x TC-DEL/-TEL 18W - Dual100950442BCS18.1-2LS-01 / 220-240 1/2x TC-DEL/-TEL 18W - Dual22BCS18.1-2LS-01 / 220-240 1/2x TC-DEL/-TEL 18W - Dual22 <td>201</td> <td>ELXc 218.871 1/2x18W - Dual</td> <td>188699</td> <td>2</td> <td></td>	201	ELXc 218.871 1/2x18W - Dual	188699	2	
PC 1/2x18 TC PRO - Single13072391PC 1/2x18 TC PRO - Dual13072392PC 1/2x18 TC TOP280000731PC 2x18 TC TOP280000742PC 1/2x18 TC PRO sr - Single21764121PC 1/2x18 TC PRO sr - Dual21764122PC 1/2x18 TC PRO sr - Dual100975442PC 1/2x18 TC PRO - 1/220-240 1/2x TC-DEL/-TEL 18W - Single100975442PC 1/2x18 TC PRO - 1/220-240 1/2x TC-DEL/-TEL 18W - Dual100950441PC 1/2x18 TC S - Dual10950442PC 1/2x18 TC S - Dual10950442PC 1/2x18 TC S - Dual10950442PC 1/2x18 TC S - Dual10950441PC 1/2x18 TC S - Dual10950442PC 1/2x18 TC S - Dual1PC 1/2x18 TC S - Dual137968/18PC 1/2x18 TC S - Dual13796		PC 1/2x18 TC PRO sr - Single	22176416	1	
P6PC 1/2x18 TC PRO - Dual13072392PC 1/2x18 TC TOP280000731PC 2x18 TC TOP28000742PC 1/2x18 TC PRO sr - Single221764121PC 1/2x18 TC PRO sr - Dual21764122PC 1/2x18 TC PRO sr - Dual21764122BC S18.1-2Q-01 /220-240 1/2x TC-DEL/-TEL 18W - Single100975441BC S18.1-2Q-01 /220-240 1/2x TC-DEL/-TEL 18W - Dual100975442BC S18.1-2Q-01 /220-240 1/2x TC-DEL/-TEL 18W - Dual100950441BC S18.1-2L-S-01 /220-240 1/2x TC-DEL/-TEL 18W - Single100950441BC S18.1-2L-S-01 /220-240 1/2x TC-DEL/-TEL 18W - Dual100950441BC S18.1-2L-S-01 /220-240 1/2x TC-DEL/-TEL 18W - Dual100950442BC S18.1-2L-S-01 /220-240 1/2x TC-DEL/-TEL 18W - Dual10095042BC S18.1-2L-S-01 /200-240 1/2x TC-DEL/-TEL 18W - DUAL<		PC 1/2x18 TC PRO sr - Dual	22176416	2	
PC 2x18 TC TOP28000742PC 1/2x18 TC PRO sr - Single21764121PC 1/2x18 TC PRO sr - Dual21764122PC 1/2x18 TC PRO sr - Dual00975441BCS18.1-2Q-01 /22 -240 1/2x TC-DEL/-TEL 18W - Single100975442BCS18.1-2Q-01 /22 -240 1/2x TC-DEL/-TEL 18W - Dual100975442BCS18.1-2LS-01 /22 -240 1/2x TC-DEL/-TEL 18W - Dual100950441BCS18.1-2LS-01 /22 -240 1/2x TC-DEL/-TEL 18W - Dual100950442BCS18.1-2LS-01 /22 -240 1/2x TC-DEL/-TEL 18W - Dual137968/181BCS18.1-2LS-01 /22 -240 1/2x TC-DEL/-TEL 18W - Dual137968/181BCS18.1-2LS-01 /22 -240 1/2x TC-DEL/-TEL 18W - DUAL137968/182BCS18.1-2LS-01 /22 -240 1/2x		PC 1/2x18 TC PRO - Single	1307239	1	
PC 2x18 TC TOP28000742PC 1/2x18 TC PRO sr - Single21764121PC 1/2x18 TC PRO sr - Dual21764122PC 1/2x18 TC PRO sr - Dual00975441BCS18.1-2Q-01 /22 -240 1/2x TC-DEL/-TEL 18W - Single100975442BCS18.1-2Q-01 /22 -240 1/2x TC-DEL/-TEL 18W - Dual100975442BCS18.1-2LS-01 /22 -240 1/2x TC-DEL/-TEL 18W - Dual100950441BCS18.1-2LS-01 /22 -240 1/2x TC-DEL/-TEL 18W - Dual100950442BCS18.1-2LS-01 /22 -240 1/2x TC-DEL/-TEL 18W - Dual137968/181BCS18.1-2LS-01 /22 -240 1/2x TC-DEL/-TEL 18W - Dual137968/181BCS18.1-2LS-01 /22 -240 1/2x TC-DEL/-TEL 18W - DUAL137968/182BCS18.1-2LS-01 /22 -240 1/2x	ONIC	PC 1/2x18 TC PRO - Dual	1307239	2	
PC1/2x18 TC PRO sr - Single PC1/2x18 TC PRO sr - Dual221764121BCS18.1-2Q-01 / 220-240 1/2x TC-DEL/-TEL 18W - Single100975441BCS18.1-2Q-01 / 220-240 1/2x TC-DEL/-TEL 18W - Dual100975442BCS18.1-2LS-01 / 220-240 1/2x TC-DEL/-TEL 18W - Dual100950441BCS18.1-2LS-01 / 220-240 1/2x TC-DEL/-TEL 18W - Dual100950442BCS18.1-2LS-01 / 220-240 1/2x TC-DEL/-TEL 18W - Dual100950442BCS18.1-2LS-01 / 220-240 1/2x TC-DEL/-TEL 18W - Dual100950442BCS18.1-2LS-01 / 220-240 1/2x TC-DEL/-TEL 18W - Dual100950442BC11/2x18TCs - Single L1/2x18TCs - Dual12BC11/2x18TCs - Dual12BC11/2x18TCs - Single L1/2x18TCs - Dual12BC11/2x18TCs - Single 	TRID	PC 1x18 TC TOP	28000073	1	
PC 1/2x18 TC PR0 sr - Dual21764122BCS18.1-2Q-01 / 220-240 1/2x TC-DEL/-TEL 18W - Single100975441BCS18.1-2Q-01 / 220-240 1/2x TC-DEL/-TEL 18W - Dual100975442BCS18.1-2LS-01 / 220-240 1/2x TC-DEL/-TEL 18W - Single100950441BCS18.1-2LS-01 / 220-240 1/2x TC-DEL/-TEL 18W - Dual100950442BCS18.1-2LS-01 / 220-240 1/2x TC-DEL/-TEL 18W - Dual10095042BCS18.1-2LS-01 / 220-240 1/2x TC-DEL/-TEL 18W - Dual10095042BCS18.1-2LS-01 / 220-240 1/2x TC-DEL/-TEL 18W - Dual137968/1181BCS18.1-2LS-01 / 220-240 1/2x TC-DEL/-TEL 18W - DUAL137968/1181BCS18.1-2LS-01 / 220-240 1/2x TC-DEL/-TEL 18W - DUAL137968/1182BCS18.1-2LS-01		PC 2x18 TC TOP	28000074	2	
BC318.1-2Q-01 / 220-240 1/2x TC-DEL/-TEL 18W - Single 10097544 1 BC518.1-2Q-01 / 220-240 1/2x TC-DEL/-TEL 18W - Dual 10097544 2 BC518.1-2LS-01 / 220-240 1/2x TC-DEL/-TEL 18W - Dual 10097544 2 BC518.1-2LS-01 / 220-240 1/2x TC-DEL/-TEL 18W - Dual 10095044 1 BC518.1-2LS-01 / 220-240 1/2x TC-DEL/-TEL 18W - Dual 10095044 2 BC518.1-2LS-01 / 220-240 1/2x TC-DEL/-TEL 18W - Dual 10095044 2 BC518.1-2LS-01 / 220-240 1/2x TC-DEL/-TEL 18W - Dual 10095044 2 BC518.1-2LS-01 / 220-240 1/2x TC-DEL/-TEL 18W - Dual 10095044 2 BC518.1-2LS-01 / 220-240 1/2x TC-DEL/-TEL 18W - Dual 10095044 2 BC11/2x18TCS - Single Income 1 EL1/2x18TCS - Dual 1 2 MBQ 118/2 MBQ 118/2 137968/118 1 MBQ 218/2 137968/18 2 1		PC 1/2x18 TC PRO sr - Single	22176412	1	
BCS18.1-2Q-01 / 220-240 1/2x TC-DEL/-TEL 18W - Dual 10097544 2 BCS18.1-2LS-01 / 220-240 1/2x TC-DEL/-TEL 18W - Single 10095044 1 BCS18.1-2LS-01 / 220-240 1/2x TC-DEL/-TEL 18W - Dual 10095044 2 BCS18.1-2LS-01 / 220-240 1/2x TC-DEL/-TEL 18W - Dual 10095044 2 BCS18.1-2LS-01 / 220-240 1/2x TC-DEL/-TEL 18W - Dual 10095044 2 BCS18.1-2LS-01 / 220-240 1/2x TC-DEL/-TEL 18W - Dual 10095044 2 BCS18.1-2LS-01 / 220-240 1/2x TC-DEL/-TEL 18W - Dual 10095044 2 BCS18.1-2LS-01 / 220-240 1/2x TC-DEL/-TEL 18W - Dual 10095044 2 BCS18.1-2LS-01 / 220-240 1/2x TC-DEL/-TEL 18W - Dual 10095044 2 BCS18.1-2LS-01 / 220-240 1/2x TC-DEL/-TEL 18W - Dual 10095044 2 BCS18.1-2LS-01 / 220-240 1/2x TC-DEL/-TEL 18W - Dual 1 2 BCS18.1-2LS-01 / 220-240 1/2x TC-DEL/-TEL 18W - Dual 137968/118 1 BCS18.1-2LS-01 / 220-240 1/2x TC-DEL/-TEL 18W - Dual 137968/118 1 BCS18/2 2 2 2 2		PC 1/2x18 TC PRO sr - Dual	22176412	2	
BL1/2x18TCs - Single I EL1/2x18TCs - Dual I MBQ 118/2 137968/118 MBQ 218/2 137968/118 Image: Single Contract 137968/118	0	BCS18.1-2Q-01 / 220-240 1/2x TC-DEL/-TEL 18W - Single	10097544	1	
BL1/2x18TCs - Single I EL1/2x18TCs - Dual I MBQ 118/2 137968/118 MBQ 218/2 137968/118 Image: Single Contract 137968/118	ПЕ	BCS18.1-2Q-01 / 220-240 1/2x TC-DEL/-TEL 18W - Dual	10097544	2	
BL1/2x18TCs - Single I EL1/2x18TCs - Dual I MBQ 118/2 137968/118 MBQ 218/2 137968/118 Image: Single Contract 137968/118	Нg	BCS18.1-2LS-01 / 220-240 1/2x TC-DEL/-TEL 18W - Single	10095044	1	
MBQ 118/2 MBQ 128/2 137968/118 1 MBQ 218/2 137968/128 2 1	BA	BCS18.1-2LS-01 / 220-240 1/2x TC-DEL/-TEL 18W - Dual	10095044	2	
MBQ 118/2 MBQ 128/2 137968/118 1 MBQ 218/2 137968/128 2 1	VAR	EL1/2x18TCs - Single		1	
P MBQ 218/2 137968/218 2	HEL	EL1/2x18TCs - Dual		2	
		MBQ 118/2	137968/118	1	
BCC 121 137946HTC 1	10	MBQ 218/2	137968/218	2	
		BCC 121	137946HTC	1	

General note Philips CorePro LED PLC

General notes: Refer to the product reference number in the header of the columns to use this product-ballast compatibility list.

Please note that Philips CorePro LED PLC 4P are only tested with HF ballast on AC operation. The performance of Philips CorePro LED PLC 4P on HF ballasts with DC operation is not tested and is therefore not guaranteed. Philips CorePro LED PLC 4P range is designed to work on HF ballasts only. For EM ballasts configuration, please contact a Philips sales representative for more information on our EM compatible range.

This document is for information purposes only and must be treated as recommendation. Philips will not accept claims for any damage caused by not implementing the recommendations in this document. Philips does not accept any responsibility, warranty or liability when using Philips CorePro LED PLC 4P with ballasts not mentioned in this list, or when using successor models of the tested ballasts. Although Philips aims to provide the most accurate information and test results from controlled experiments the results may vary in different applications. This document focuses on the behaviour of above mentioned Philips CorePro LED PLC 4P. Please also check and follow the instructions of HF ballast manufacturers for installation instructions.

Always check the latest update of the compatibility list on www.philips.com/ledtube

Dimming: Philips CorePro LED PLC 4P are not developed for dimming therefore the performance cannot be guaranteed in a dimming application. In case of usage of a non-dimmable product in a dimmable application, warranty does not apply.

PHILIPS

Philips CorePro LED PLC 9.0W 8xx 4P G24q-3

Ballast Compatibility



KEY

K	EY				
		Ballast is compatible			This document is for information purposes and must be treated as
		Ballast is not compatible, will not work according to Philips claimed specifications			recommendation. Philips attempted to provide best results, results are generated in lab controlled environment and may differ from actual application conditions
					application conditions
					CorePro LED PLC 9W 8xx 4P G24q-3 Model number: 9290012008 9290012009
		Ballast type	10nc	Lamps on ballast	AC (50Hz) on HF Ballast Compatible
		HF-P 226 PL-T/C III 220-240V 50/60Hz	9137006488	2	
		HF-P 126 PL-T/C III 220-240V 50/60Hz	9137006487	1	
		HF-P122-42 PL-T/C/L/TL5C EII 220-240V	9137006307	1	
		HF-P 2 22-42 PL-T/C/L/TL5C EII 220-240V	9137006308	2	
	S	HF-S 226 PL-T/C II SR 220-240V		2	
	SHILIPS	HF-S 226 PL-T/C/L/TL5C II SR 220-240V		2	
		HF-S 126 PL-T/C/L/TL5C II SR 220-240V	9137130357	1	
		HF-P 126 PL-T/C 26		1	
		HF-P 226 PL-T/C 220-240		2	
		HF-P 26-42 PL-T/C 220-240		2	
		QTP-M 1x26-42		1	
		QTP-M 2x26-32 - Dual		2	
		QTP-M 2x26-32 - Single		1	
		QT-M 2x26-42/220-240 S		2	
	_	QTP-T/E 1x26-42, 2x26 - Dual		2	
	OSRAM	QTP-T/E 1x26-42, 2x26 - Single		1	
	00	QT-ECO T/E 2X26/220-240		2	
		QT-ECO 1X26/220240 S		1	
		Quicktronic QT-T/E 2x26 / 230-240		2	
		QT-M 2x26-32/230-240 S		2	
		QT-M 1x26-42/220-240 S		1	
		ELXc 142.872 2x26W 1x26/32/42W - Dual	188700	2	
	VOSSLOH- SCHWABE	ELXc 142.872 2x26W 1x26/32/42W - Single	188700	1	
	CHW	ELXc 242.837 2x26/32/42W	188643	2	
	> v	ELXs 126.906 1x26	188667	1	
		PC 1/2x26 TC PRO sr - Single	22176417	1	
		PC 1/2x26 TC PRO sr - Dual	22176417	2	
	U	PC 1/2 x 26-42 TC PRO - Single	22176408	1	
	DONIC	PC 1/2 x 26-42 TC PRO - Dual	22176408	2	
	TRIC	PC 2x26-42 TC PRO	22176410	2	
		PC 1x26-42 TC TOP	28000075	1	
		PC 2x26 TC TOP	28000076	2	
		BCS42.1/26.2LS-01/220-240 1/2x TC-DEL/-TEL 26W - Single	10095045	1	
	0	BCS42.1/26.2LS-01/220-240 1/2x TC-DEL/-TEL 26W - Dual	10095045	2	
	ы	BCS42.1/26.2Q-01/220-240 1/2x TC-DEL/-TEL 26W - Single	10097545	1	
	BAG HUECO	BCS42.1/26.2Q-01/220-240 1/2x TC-DEL/-TEL 26W - Dual	10097545	2	
	BA	BCS70.1/42.2Q-01/220-240 1/2x TC-DEL/-TEL 26W - Single	10097546	1	
		BCS70.1/42.2Q-01/220-240 1/2x TC-DEL/-TEL 26W - Dual	10097546	2	
	~	EL1/2x18-42TCs - Single		1	
	HELVAR	EL1/2x18-42TCs - Dual		2	
	Ξ	EL2x32/42TCs		1	
		MBQ 226/2	137968/226	2	
		MBQ 220/2 MBQ 142/2	137968/142	1	
	5	MBQ 242/2 - Single	137962/242	1	

General note Philips CorePro LED PLC

MBQ 242/2 - Single

MBQ 242/2 - Dual

BCC 126

4

General notes: Refer to the product reference number in the header of the columns to use this product-ballast compatibility list.

Please note that Philips CorePro LED PLC 4P are only tested with HF ballast on AC operation. The performance of Philips CorePro LED PLC 4P on HF ballasts with DC operation is not tested and is therefore not guaranteed. Philips CorePro LED PLC 4P range is designed to work on HF ballasts only. For EM ballasts configuration, please contact a Philips sales representative for more information on our EM compatible range.

2

1

137962/242

137962/242

137949HTC

This document is for information purposes only and must be treated as recommendation. Philips will not accept claims for any damage caused by not implementing the recommendations in this document. Philips does not accept any responsibility, warranty or liability when using Philips CorePro LED PLC 4P with ballasts not mentioned in this list, or when using successor models of the tested ballasts. Although Philips aims to provide the most accurate information and test results from controlled experiments the results may vary in different applications. This document focuses on the behaviour of above mentioned Philips CorePro LED PLC 4P. Please also check and follow the instructions of HF ballast manufacturers for installation instructions.

Always check the latest update of the compatibility list on $\underline{www.philips.com/ledtube}$

Dimming: Philips CorePro LED PLC 4P are not developed for dimming therefore the performance cannot be guaranteed in a dimming application. In case of usage of a non-dimmable product in a dimmable application, warranty does not apply.

PHILIPS

Ballast is not compatible

Philips CorePro LED PLL HF 16W 8xx 4P 2G11

Ballast Compatibility

KEY

*

Ballast is compatible
Ballast is compatible, light output may differ >10% compared to specifications

This document is for information purposes and must be treated as recommendation. Philips attempted to provide best results, results are generated in lab controlled environment and may differ from actual application conditions

				CorePro LED PLL HF 16W 8xx 4P 2G11 Model number: 9290013815 9290013816 9290013816
	Ballast type	10nc	Lamps on ballast	AC (50Hz) on HF Ballast Compatible
	HF-P 136 TL-D III 220-240V 50/60Hz IDC	913713031566	1	
	HF-P 236 TL-D III 220-240V 50/60Hz IDC	913713031666	2	
	HF-S 136 TL-D II 220-240V 50/60Hz	913713032166	1	
	HF-S 236 TL-D II 220-240V 50/60Hz	913713032466	2	
	HF-E 136 TL-D II 220-240 50/60Hz	913713041066	1	
	HF-E 236 TL-D II 220-240 50/60Hz	913713041166	2	
	HF-S 336 TL-D II 220-240V 50/60Hz	913713032766	3	
	HF-Pi 1 14/21/24/39 TL5 EII 220-240V	913700624066	1	
	HF-Pi 2 14/21/24/39 TL5 EII 220-240V	913700624266	2	
	HF-P136 PLL EII 220-240V 50/60Hz	913700192066	1	
Sdilihd	HF-P 236 PLL EII 220-240V 50/60Hz	913700192366	2	
H	HF-P 136 PLL III 220-240V 50/60Hz	913713028466	1	
	HF-P 236 PLL III 220-240V 50/60Hz	913713028566	2	
	HF-P 136 PLL 220-240	9137001145	1	
	HF-R 236 TL-D EII 220-240V 50/60Hz	913700609366	2	•
	HF-Regulator 236 PLL EII 220-240V 50/60Hz	913700620066	2	•
	HF-R 136 PLL 220-240	9137001156	1	•
	HF-R 236 PLL 220-240	9137001157	2	•
	HF-Ri TD I 14/21/24/39 TL5 E+	9137006983	1	•
	HF-B 136 TLD 220-240	9137001122	1	
	HF-B 136 TLD EII 220-240	9137001926	1	
	HF-B 236 TLD EII 220-240	9137001928	2	
	Qti 1x14/24/21/39 GII		1	
	Qti 2x14/24/21/39 GII		2	
	QT-M 2x26-42/220-240 S		2	
	QTP-DL 1x36-40		1	
5	QTP-DL 2x36-40		2	
OSRAM	QTP-M 1x26-42		1	
0	QTP-M 2x26-32		2	
	QTP-OPTIMAL 2x18-40		2	
	Quictronic QT 1x36/230		1	
	QT-M 1x26-42/230-240 S		1	
	QT-M 2x26-32/230-240 S		2	
	EL1x39/36ngn5		1	
	EL2x39/36ngn5		2	
AR	EL2x39/36s		2	
HELVAR	EL1/2x36/38TCs - Single		1	
	EL1/2x36/38TCs - Single		1	
	EL1/2x18-42TCs - Single		1	
	ELXc 140.862	188140	1	
В	ELXc 240.863	188616	2	
IWAI	ELXc 142.872	188700	1	
VOSSLOH SCHWABE	ELXc 242.837	188643	2	
SLOF	ELXc 236.208	188705	2	
vos	ELXc 142.876	188888	1	
	ELXc 242.877	188889	2	
	PC 1/36 TCL PRO	22176141	1	
	PC 2/36 TCL PRO	22176170	2	
	PC 3/36 T8 PRO	22176231	3	
<u>ں</u>	PC 1/14-35/24/39 T5 PRO-M lp	22176182	1	
TRIDONIC	PC 2/14-21/24/39 T5 PRO-M lp	22176185	2	
TRI	PC 1x36 T8 TEC	87500258	1	
	PC 2x36 T8 TEC	87500259	2	
	PC 2x36/4x18 T8 TEC	87500260	2	
	PCA 2/36 TCL ECO	22085516	2	

PHILIPS

Philips CorePro LED PLL HF 16W 8xx 4P 2G11



Ballast Compatibility

KEY

	Ballast is compatible	This day and the fact of the state of the st
*	Ballast is compatible, light output may differ >10% compared to specifications	This document is for information purposes and must be treated as recommendation. Philips attempted to provide best results, results are
		generated in lab controlled environment and may differ from actual application conditions
	Ballast is not compatible	application conditions
		CorePro LED PLL HF 16W 8xx 4P 2G11

				Model number: 9290013815 9290013816 9290013817
	Ballast type	10nc	Lamps on ballast	AC (50Hz) on HF Ballast Compatible
	BCS38.1LS-01/220-240	10097427	1	
	BCS38.1Q-01/220-240	10097437	1	
~	BCS39.1FX-11/220-240	10077581	1	
HUECO	BCS42.1Q-01/220-240	10097535	1	
로	MLS39.1-2FR-11/220-240 - Single	10092026	1	
BAG	MLS39.1-2FR-11/220-240 - Single	10092026	1	
	BCS39.2FX-11/220-240	10077582	2	
	D58.1-23021 E	166072	1	
	BCS36.1SR-01/220-240	10051000	1	
Trilux	D58.1-23021 E		1	
ers	Direct Mains			
Others	Electro Magnetic Ballast			

General note Philips CorePro LED PLL

General notes: Refer to the product reference number in the header of the columns to use this product-ballast compatibility list.

Please note that Philips CorePro LED PLL 4P are only tested with HF ballast on AC operation. The performance of Philips CorePro LED PLL 4P on HF ballasts with DC operation is not tested and is therefore not guaranteed. Philips CorePro LED PLL 4P range is designed to work on HF ballasts only.

This document is for information purposes only and must be treated as recommendation. Philips will not accept claims for any damage caused by not implementing the recommendations in this document. Philips does not accept any responsibility, warranty or liability when using Philips CorePro LED PLL 4P with ballasts not mentioned in this list, or when using successor models of the tested ballasts. Although Philips aims to provide the most accurate information and test results from controlled experiments the results may vary in different applications. This document focuses on the behaviour of above mentioned Philips CorePro LED PLL 4P. Please also check and follow the instructions of HF ballast manufacturers for installation instructions.

Always check the latest update of the compatibility list on www.philips.com/ledtube

Dimming: Philips CorePro LED PLL 4P are not developed for dimming therefore the performance cannot be guaranteed in a dimming application. In case of usage of a non-dimmable product in a dimmable application, warranty does not apply.

PHILIPS

Philips CorePro LED PLL HF 24W (55) 8xx 4P 2G11

Ballast Compatibility

KEY

*

Ballast is compatible
Ballast is compatible, light output may differ >10% compared to specifications

Ballast is not compatible

This document is for information purposes and must be treated as recommendation. Philips attempted to provide best results, results are generated in lab controlled environment and may differ from actual application conditions

				CorePro LED PLL HF 24W 8xx 4P 2G11 Model number: 9290019204 9290019205 9290019206
	Ballast type	10nc	Lamps on ballast	AC (50Hz) on HF Ballast Compatible
	HF-E 1/2 54 TL5 II 220-240 50/60Hz	913713040866	1	
	HF-E 1/2 54 TL5 II 220-240 50/60Hz	913713040866	2	• • • • • • • • • • • • • • • • • • •
	HF-E 1/2 58 TL-D II 220-240 50/60Hz	913713040966	1	
	HF-E 1/2 58 TL-D II 220-240 50/60Hz	913713040966	2	
	HF-P 158 TL-D III 220-240V 50/60Hz IDC	913713031866	1	
	HF-P 158 TL-D III 220-240V 50/60Hz IDC UBA 2013T	913713031866	1	
	HF-P 258 TL-D III 220-240V 50/60Hz IDC	913713031966	2	
	HF-P 154/155 TL5 HO/PL-L III IDC	913713028266	1	
	HF-P 254/255 TL5 HO/PL-L III IDC	913713028366	2	
	HF-S 154 TL5 II 220-240V 50/60Hz	913713033666	1	•
	HF-S 254 TL5 II 220-240V 50/60Hz	913713033766	2	
Sali	HF-S 158 TL-D II 220-240V 50/60Hz	913713032266	1	•
SAILIHA	HF-S 258 TL-D II 220-240V 50/60Hz	913713032566	2	•
	HF-S 258 TL-D II HT 220-240V 50/60Hz	913700689966	2	
	HF-B 158 TLD EII 220-240	9137001927	1	
	HF-B 258 TLD EII 220-240	913700929	2	
	HF-Pi 1 28/35/49/54 TL5 EII 220-240V	913700624166	1	•
	HF-Pi 2 28/35/49/54 TL5 EII 220-240V	913700624366	2	•
	HF-P 155 PLL EII 220-240 50/60Hz	913700192266	1	
	HF-P 255 PLL EII 220-240V 50/60Hz	913700192566	2	
	HF-P 255 PLL EII 220-240 50/60Hz	9137006513	2	
	HF-P 155 PLL III IDC 220-240V 50/60Hz	913713028866	1	
	HF-P 155 PLL 220-240	9137001218	1	
	HF-P 255 PLL 220-240	9137001150	2	
	QT-FQ 2x80		2	
	Qti 1x35/49/80 GII		1	
	Qti 2x35/49/80 GII		2	
	QTP-DL 2x55 GII		2	
Σ	QTP-DL 1x55 GI		1	
OSRAM	QTP-DL 2x55		2	
0	QTP-FC 1x55		1	
	QT 2x55 / 230		2	
	QTP-OPTIMAL 1x54-58		1	
	QTP-OPTIMAL 2x54-58		2	
			2	
	EL1x55ngn5		1	
HELVAR	EL2x55ngn5		2	
HE	EL1x55s		1	•
	EL2x55s		2	•
	ELXc 180.866	188144	1	•
VOSSLOH	ELXc 254.865	188618	2	
OSSI	ELXc 280.538	188619	2	•
> 0	ELXc 155.378	188680	1	•
		22105200	1	
	PC 1x80 T5 PRO lp	22185209		
	PC 2x55 TCL PRO lp	22185286	2	
	PC 1/55 TCL PRO	22176169	<u> </u>	
DNIC	PC 2/55 TCL PRO	22176233	2	
TRIDONIC	PC 1/14-35/49/80 T5 PRO-M lp	22176184	1	
	PC 1x58 T8 PRO lp	22185215		
	PC 2x58 T8 PRO sl	22185218	2	
	PC 1x58 T8 TEC	87500150	1	· · · ·
	PC 2x58 T8 TEC	87500151	2	

PHILIPS

Philips CorePro LED PLL HF 24W (55) 8xx 4P 2G11

Ballast Compatibility

KEY

•	Ballast is compatible	T I. 1	
	Ballast is compatible, light output may differ >10% compared to specifications	This document is for information purposes and must be treated as recommendation. Philips attempted to provide best results, results are generated in lab controlled environment and may differ from actual application conditions	
	Ballast is not compatible		

				CorePro LED PLL HF 16W 8xx 4P 2G11 Model number: 929001381502 929001381602 929001381602
	Ballast type	10nc	Lamps on ballast	AC (50Hz) on HF Ballast Compatible
	BCS54.1FX-11/220-240	10077585	1	•
	BCS55.1Q-01/220-240/T5C	10097634	1	
•	BCS54.2FX-11/220-240	10077586	2	•
HUECO	MLS80.1/54.2FR-11/220-240	10071609	1	
F	MLS80.1/54.2FR-11/220-240	10071609	2	
BAG	BCS54.1FR-01/220/240	10075881	1	
	D58.1-23021 E	166072	1	
	D58.2-23021 E	166082	2	
	BCS58.1SR-01/220-240	10051002	1	
Trilux	D58.1-23021 E		1	
TCI	BTLT 154	137998/154	1	
Ĕ	BTLT 254	137999/54	2	•
ers	Direct Mains			
Others	Electro Magitic Ballast			

General note Philips CorePro LED PLL

General notes: Refer to the product reference number in the header of the columns to use this product-ballast compatibility list.

Please note that Philips CorePro LED PLL 4P are only tested with HF ballast on AC operation. The performance of Philips CorePro LED PLL 4P on HF ballasts with DC operation is not tested and is therefore not guaranteed. Philips CorePro LED PLL 4P range is designed to work on HF ballasts only.

This document is for information purposes only and must be treated as recommendation. Philips will not accept claims for any damage caused by not implementing the recommendations in this document. Philips does not accept any responsibility, warranty or liability when using Philips CorePro LED PLL 4P with ballasts not mentioned in this list, or when using successor models of the tested ballasts. Although Philips aims to provide the most accurate information and test results from controlled experiments the results may vary in different applications. This document focuses on the behaviour of above mentioned Philips CorePro LED PLL 4P. Please also check and follow the instructions of HF ballast manufacturers for installation instructions.

Always check the latest update of the compatibility list on $\underline{www.philips.com/ledtube}$

Dimming: Philips CorePro LED PLL 4P are not developed for dimming therefore the performance cannot be guaranteed in a dimming application. In case of usage of a non-dimmable product in a dimmable application, warranty does not apply.

PHILIPS



© 2018 Signify Holding. All rights reserved. The information provided herein is subject to change, without notice. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract.

Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V. All other trademarks are owned by Signify Holding or their respective owners.

09/2018 Data subject to change.