

# ANALOGUE TIME SWITCHES

müller VS 2x.18 - paladin 15x 220



## Overview

- Daily program
- Slim format 35 mm
- Captive setting keys
- Manual override switch Permanent ON / Permanent OFF / AUTO

## Intended use

- The device fits for the particular use of the following tasks: Illumination of private and industrial areas, street and shop-window lightening, regulation of air conditioning, flushing, motors, pumps, plants and machinery as well as to simulate presence etc.
- Operate the device in a dry room only!
- The installation must be in accordance with the instruction manual.
- The device is not qualified for security relevant tasks such as emergency doors, fire protection equipment.

## Supply voltage versions

- 230 V, 50-60 Hz
- 115 V, 50-60 Hz
- 12-24 V DC & 24-48 V, 50-60 Hz

## Order numbers

■ müller	■ paladin	
VS 20.18	151 220	Day without reserve
VS 24.18	154 220	Day with reserve

# ANALOGUE TIME SWITCHES

müller VS 2x.18 - paladin 15x 220

## Order information

	Voltage	EAN	Art. No.
<b>VS 20.18</b>	230 V 50-60 Hz	4022709214515	21451
<b>VS 24.18</b>	230 V 50-60 Hz	4022709218483	21848
<b>151 120</b>	230 V 50-60 Hz	4011732005191	00519
<b>154 120</b>	230 V 50-60 Hz	4011732005306	00530

Other supply voltage versions on request

## Technical data

Supply voltage	230 V, 50-60 Hz
Power consumption (real power)	0,4 W
Switch (potential-free)	Change-over, contact gap < 3mm (μ)
Manual override switch	Permanent ON / Permanent OFF / AUTO
Contact material	AgSnO <sub>2</sub>
Switching capacity	
resistive load:	16 A / 250 V~ at cosφ=1
inductive load:	2,5 A / 250 V~ at cosφ=0,6
Min. switching power	1.000 mW (10 V / 10 mA)
Filament Lamp, Halogen Lamp	2.000 W
Fluorescent Lamp uncompensated	1.000 W
Fluorescent Lamp series compensated	750 W
LED (230 V~) / CFL	200 W
Minimum switching interval	30 Min.
Time base	Quartz
Accuracy (at 23 °C)	±1 Sec./day
Power back-up (at 20 °C)	approx. 100 h.
Permitted ambient temperature	-5...+50 °C
Housing	self-extinguishing thermoplastic
Dimensions	45 x 35 x 58 mm
Mounting	35 mm DIN-Schiene
Type of connection	Screw terminals
Type of protection	IP 20 to DIN EN 60529
Class of protection	II when installed according to regulations
Mode of operation (DIN EN 60730-1) (DIN EN 60730-2-7)	1 BSTU
Degree of contamination (DIN EN 60730-1)	2
Rated surge voltage (DIN EN 60730-1)	4 kV

Rights to technical amendments reserved / Technische Änderungen vorbehalten  
Droits de modifications techniques réservés / Suscettibile di errori e modifiche

